

Delock Adapter 2.92 jack > 2.92 jack 40 GHz

Description

This adapter by Delock is suitable for connecting components of radio frequency technology.

Extremely precise manufacturing results in high performance up to 40 GHz.



Item no. 65922

EAN: 4043619659227

Country of origin: China

Package: Poly bag

Specification

- Connectors:
 - 1 x 2.92 jack >
 - 1 x 2.92 jack
- Material: stainless steel X8CrNiS18-9
- Thread type: 1/4" - 36 UNS - 2A
- Impedance: 50 Ohm
- Frequency range: DC - 40 GHz
- VSWR: 1.2
- Operating temperature: -55 °C ~ 155 °C
- Length incl. connectors: ca. 19.12 mm
- Diameter: ca. 6.4 mm

System requirements

- Device with one free 2.92 port

Package content

- RF Adapter

Interface

| | |
|--------------|---------------|
| Connector 1: | 1 x 2.92 jack |
| Connector 2: | 1 x 2.92 jack |

Technical characteristics

| | |
|------------------------|-----------------|
| Impedance: | 50 Ω |
| Operating temperature: | -55 °C ~ 155 °C |

Physical characteristics

| | |
|-------------------|-----------------------------|
| Housing material: | Stainless steel X8CrNiS18-9 |
| Diameter: | 6.4 mm |
| Length: | 19:12 mm |
| Thread type: | 1/4" - 36 UNS - 2A |