

# Mini DisplayPort 1.4 to DisplayPort adapter with latch 8K 60 Hz

## Description

This mini DisplayPort adapter by Delock can be used to connect a DisplayPort monitor to graphics cards with mini DisplayPort ports that have special notches in the slot bracket above the ports. The additional latch of the plug of the adapter snaps into the notch and prevents the adapter from being pulled out unintentionally.



**Item no. 65978**

EAN: 4043619659784

Country of origin: China

Package: Retail Box

## Technical details

- Connectors:
  - 1 x mini DisplayPort male with latch >
  - 1 x DisplayPort female
- DisplayPort 1.4 specification
- Downwards compatible to DisplayPort 1.3, 1.2 and 1.1
- Pin 20 is connected (supports 3.3 V)
- Cable gauge: 32 AWG
- Cable diameter: ca. 4.8 mm
- Contacts gold-plated
- LS0H (halogen-free)
- Transmission of audio and video signals
- Data transfer rate up to 32.4 Gb/s
- Resolution up to:
  - Display with DSC support: 7680 x 4320 @ 60 Hz
  - Display without DSC support: 7680 x 4320 @ 30 Hz
  - (depending on the system and the connected hardware)
- Supports HDR
- Supports HDCP 1.4 and 2.2
- Up to 1536 kHz audio sampling rate
- Cable length incl. connectors: ca. 15 cm
- Colour: black

---

## System requirements

- A free mini DisplayPort female

---

## Package content

- Adapter mini DisplayPort to DisplayPort

---

## Images



## General

Specification:	DisplayPort 1.4 HDCP 1.4 HDCP 2.2 HDR10
----------------	--

## Interface

Connector 1:	1 x mini DisplayPort male
Connector 2:	1 x DisplayPort female

## Technical characteristics

Data transfer rate:	32.4 Gb/s
Maximum screen resolution:	7680 x 4320 @ 60 Hz

## Physical characteristics

Cable length incl. connectors:	15 cm
Pin finishing:	gold-plated
Cable gauge:	32 AWG
Colour:	black
Cable diameter:	4.8 mm

## Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de