

Delock Express Card > 1 x FireWire A, 2 x FireWire B

Description

This adapter complies with the Express Card 34 mm standard. It expands a laptop by two FireWire B ports, as well as one FireWire A port to connect FireWire devices such as external enclosure, adapter etc.



Item no. 66006

EAN: 4043619660063

Country of origin: Taiwan,
Republic of China

Package: White Box

Specification

- Connector:
Express Card 34 mm >
1 x FireWire 1394A 6 pin female
2 x FireWire 1394B 9 pin female
1 x 12 V DC female 3.5 x 1.35 mm
- Chipset: Texas Instruments XIO2213BZAY
- Data transfer rate up to 800 Mb/s
- Plug & Play

System requirements

- Windows 7/7-64/8/8-64/8.1/8.1-64/10/10-64
- Laptop with a free Express Card slot

Package content

- Express Card FireWire

Images



General

Supported operating system:	Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-Bit Windows 8.1 64-Bit
-----------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------

Interface

External:	1 x 12 V DC female 3.5 x 1.35 mm 1 x FireWire 1394A 6 pin female 2 x FireWire 1394B 9 pin female
Internal:	1 x Express Card 34 mm

Technical characteristics

Chipset:	Texas Instruments XIO2213BZAY
Data transfer rate:	up to 800 Mb/s