

# Delock DIP sliding switch 8-digit 2.54 mm pitch THT vertical blue 10 pieces

## Description

This DIP sliding switch by Delock is suitable for the through-hole mounting on a PCB.

#### **THT Assembly Technology**

The attached soldering pins on the DIP switch can be inserted through contact holes on a PCB and soldered from the bottom side. The switching rows are used to set configurations and to change parameters.

#### **Multifunctional application**

The DIP switch is mainly used in telecommunications, computers and measuring.



10 x

#### Item no. 66100

EAN: 4043619661008 Country of origin: China Package: Tube

# Specification

- Connectors:
  - 2 x 8 soldering pin
- Number of positions: 8
- Pitch: 2.54 mm
- Switch position: on / off
- Switching rating: 25 mA, 24 VDC
- Insulation resistance: 100  $M\Omega\,/\,500$  VDC
- Withstanding voltage: 300 VAC / 1 minute
- Soldering temperature: 250 °C for ca. 3 5 seconds
- Environmental temperature: -40 °C ~ 85 °C
- Operating temperature: -20 °C ~ 85 °C
- Material: plastic
- Colour: blue
- Dimensions (LxWxH): ca. 21.7 x 9.9 x 5.6 mm




# Package content

• 10 x DIP sliding switch

## Images









## General

Interface	

connector: 2 x 8 soldering pin
--------------------------------

## **Technical characteristics**

Storage temperature:	-40 °C ~ 85 °C
Operating temperature:	-20 °C ~ 85 °C
Resistor:	100 MΩ / 500 VDC

# **Physical characteristics**

Pitch distance:	2.54 mm
Material:	Plastic
Length:	21.7 mm
Width:	9.9 mm
Height:	5.6 mm
Switch:	On / Off
Colour:	blue