

# Delock DIP flip switch piano 8-digit 2.54 mm pitch THT vertical red 2 pieces

## **Description**

This DIP flip switch by Delock is suitable for the through-hole mounting on a PCB.

#### **THT Assembly Technology**

The attached soldering pins on the DIP switch can be inserted through contact holes on a PCB and soldered from the bottom side. The switching rows are used to set configurations and to change parameters.

### **Multifunctional application**

The DIP switch is mainly used in telecommunications, computers and measuring.



### Item no. 66128

EAN: 4043619661282 Country of origin: China

Package: Tube

## **Specification**

- Connectors:
  - 2 x 8 soldering pin
- Number of positions: 8
- Pitch: 2.54 mm
- Switch position: on / off
- Switching rating: 25 mA, 24 VDC
- Insulation resistance: 100 M $\Omega$  / 500 VDC
- Withstanding voltage: 300 VAC / 1 minute
- Soldering temperature: 250 °C for ca. 3 5 seconds
- Environmental temperature: -40 °C ~ 85 °C
- Operating temperature: -20 °C ~ 85 °C
- · Material: plastic
- · Colour: red
- Dimensions (LxWxH): ca. 21.9 x 10.8 x 9.4 mm




# Package content

• 2 x DIP flip switch

# **Images**









## General

## Interface

2 x 8 soldering pin connector:

## **Technical characteristics**

Storage temperature:	-40 °C ~ 85 °C
Operating temperature:	-20 °C ~ 85 °C
Resistor:	100 MΩ / 500 VDC

# **Physical characteristics**

Pitch distance:	2.54 mm
Material:	Plastic
Length:	21.9 mm
Width:	10.8 mm
Height:	9.4 mm
Switch:	On / Off
Colour:	red