

# Delock DIP sliding switch 2-digit 2.54 mm pitch THT angled red 5 pieces

## Description


This DIP sliding switch by Delock is suitable for the solder mounting on a PCB.

## THT Assembly Technology

The attached soldering pins on the DIP switch can be inserted through contact holes on a PCB and soldered from the bottom side. The switching rows are used to set configurations and to change parameters.

## Multifunctional application

The DIP switch is mainly used in telecommunications, computers and measuring.



5 x

**Item no. 66150**

EAN: 4043619661503

Country of origin: China

Package: Tube

## Specification


- Connectors:  
2 x 2 soldering pin
- Number of positions: 2
- Pitch: 2.54 mm
- Switch position: on / off
- Switching rating: 25 mA, 24 VDC
- Insulation resistance: 100 MΩ / 500 VDC
- Withstanding voltage: 300 VAC / 1 minute
- Soldering temperature: 250 °C for ca. 5 seconds
- Environmental temperature: -40 °C ~ 85 °C
- Operating temperature: -20 °C ~ 85 °C
- Material: plastic
- Colour: red
- Dimensions (LxWxH): ca. 9.9 x 6.5 x 5.4 mm

## Package content

- 5 x DIP sliding switch

---

## Images



## General

Mounting type:	Soldering
----------------	-----------

## Interface

connector:	2 x 2 soldering pin
------------	---------------------

## Technical characteristics

Storage temperature:	-40 °C ~ 85 °C
Operating temperature:	-20 °C ~ 85 °C
Resistor:	100 MΩ / 500 VDC

## Physical characteristics

Pitch distance:	2.54 mm
Material:	Plastic
Length:	9.9 mm
Width:	6.5 mm
Height:	5.4 mm
Switch:	On / Off
Colour:	red