

# Delock Adapter USB 2.0 Type-A to 1 x Serial RS-422/485 DB9

## Description

This USB 2.0 Type-A to serial adapter by Delock provides an RS-485 port for meters, POS systems, printers, modems, IoT devices, etc.



## Specification

- Connectors:  
1 x USB 2.0 Type-A male >  
1 x serial RS-422/485 DB9 male with screws
- Chipset: FTDI FT232
- Data transfer rate up to 921.6 Kbps
- Signals: T/R+, T/R-, RXD+, RXD-, GND
- Parity: even, odd, none, mark, space
- Stop bits: 1, 2
- Databits: 7, 8
- FIFO: 128 Byte - RX
- FIFO: 256 Byte - TX
- Cable length incl. connectors: ca. 80 cm

## System requirements

- Linux Kernel 2.6 or above
- Mac OS 10.9 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64/11
- PC or laptop with a free USB Type-A port

## Package content

- USB 2.0 to 1 x serial RS-422/485 adapter
- USB 2.0 extension cable
- Driver CD
- User manual


## Item no. 66286

EAN: 4043619662869

Country of origin: China

Package: Retail Box

## Images



General	
Function:	Plug & Play
Specification:	RS-422 / RS-485 (EIA / TIA) USB 2.0
Supported operating system:	Linux Kernel 2.6 or above Mac OS 10.9 or above Windows 10 32-bit Windows 10 64-bit Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows Server 2012 R2 Windows Server 2016 Windows 11
Interface	
Connector 1:	1 x USB 2.0 Type-A male
Connector 2:	1 x Serial RS-422/485 DB9 male
Technical characteristics	
Chipset:	FTDI 232R
Data transfer rate:	up to 921.6 Kbps
FIFO:	128 byte 256 Byte
Data transmission:	asynchronous Bi-directional Half duplex full duplex differential
UART:	USB to serial UART
Physical characteristics	
Cable colour:	black
Cable length incl. connector:	80 cm
Pin finishing:	gold-plated
Shielding:	double
Colour:	black