

Delock Professional USB Condenser Microphone Set for Podcasting and Gaming

Description

This professional USB condenser microphone by Delock can be used for high-quality voice and vocal recordings.

Optimal recordings

The microphone has a 16 mm condenser and a cardioid polar pattern (unidirectional) and therefore ideally captures the sound. Due to high power, low self-noise and precise performance, even the finest sounds are recorded crystal clear.

Dual Layer Pop Filter & Windscreen

Due to the included dual layer pop filter and the windscreen, the recording quality is further optimized. Annoying wind noises are optimally filtered.

High sampling rate

Typical USB microphones work with 16 Bit and 44 KHz. The Delock microphone offers a sampling rate of 24 Bit and 192 kHz, so it is possible to record in Hi-Fi studio quality.

Plug & Play

Due to USB Plug & Play the microphone is ready to use immediately, no driver installation is needed. The microphone works with all common operating systems such as Windows, Mac OS, Chrome OS and Linux.

Stable & adjustable stand

The stand ensures that the microphone is stable on the table. With the telescopic function, the microphone can be adjusted to the preferred height.



Specification

- Connector: 1 x USB 2.0 Type-B female
- Directivity: unidirectional
- Sensitivity: -38 dB +/- 3 dB
- Frequency range: 30 Hz - 16 kHz
- Sample rate: 24 Bit / 192 kHz
- Signal-to-noise ratio (SNR): ca. 70 dB
- Self-Noise: max. 16 dBA
- Sound pressure level (SPL): max. 120 dB
- Dual-Layer pop filter: Ø 120 mm
- Stand: Ø ca. 130 mm (ca. 600 g)
- USB bus powered
- Plug & Play

System requirements

- Chrome OS
- Linux Kernel 4.4 or above
- Mac OS 10.9 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

Package content

- USB microphone
- USB 2.0 Type-A to USB 2.0 Type-B cable, length ca. 2.5 m
- Shock mount (spider)

Item no. 66300

EAN: 4043619663002

Country of origin: China

Package: Retail Box

- Telescopic rod
- Stand
- Pop filter
- Windscreen
- User manual

Images



General

Function:	Plug & Play
Supported operating system:	Chrome OS Linux Kernel 4.4 or above Mac OS 10.10 or above Windows 10 32-bit Windows 10 64-bit Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit

Interface

connector:	1 x USB 2.0 Type-A male
------------	-------------------------

Technical characteristics

Frequency range:	30 Hz - 16 kHz
Voltage:	USB bus powered
Sensibility:	-38 dB +/- 3 dB
Sample rate:	24 Bit / 192 kHz
Signal noise ratio (SNR):	ca. 70 dB
Directivity:	uni-directional

Physical characteristics

Cable length:	2.5 m
Colour:	black