

## Delock D-Sub 37 male with insulation displacement 2 pieces

### Description

This D-Sub 37 male with insulation displacement by Delock can be used to mount flat cables with 37 pin and a pitch of 1.27 mm. The D-Sub connectors for flat cables are often used e.g. in industry, telecommunications and for hobby applications.



### Note

For pressing the flat cable into the insulation displacement, it is recommended to use the Delock installation tool 86469.

### Specification

- Connectors:
  - 1 x D-Sub 37 male (2 rows) with nuts with insulation displacement
  - 1 x press-in clip
  - 1 x strain relief clip
- Suitable for flat cable with 1.27 mm pitch
- Operating temperature: -40 °C ~ 105 °C
- Colour: blue
- Dimensions (LxWxH): ca. 69,3 x 17,5 x 12,8 mm

### System requirements

- A free D-Sub 37 pin female and flat cable 37 pin with 1.27 mm pitch

### Package content

- 2 x D-Sub 37 male with insulation displacement

### Item no. 66594

EAN: 4043619665945

Country of origin: China

Package: Zip poly bag

**Interface**

Connector 1:	1 x press-in clip
	1 x strain relief clip
	1 x Sub-D37 male (2 rows) with nuts with insulation displacement

**Technical characteristics**

Operating temperature:	-40 °C ~ 105 °C
------------------------	-----------------

**Physical characteristics**

Pitch distance:	1.27 mm
Length:	69.3 mm
Width:	17.5 mm
Height:	12.8 mm
Colour:	blue