

Delock Crimpbox 120 pieces 50 Ohm with SMA, SMB and RP-SMA connectors

Description

This high-quality box by Delock contains various high-frequency technology connectors for connecting components.

SMA connectors

SMA connectors are often used in the fields of telecommunications, data communication by means of antenna technology, but also in automation.

Thanks to the screw locking, they are mechanically very robust despite their small size.

RP-SMA connectors

RP-SMA, or reverse SMA, has a hollow tube and no metal pin, in contrast to the SMA connector.

The RP-SMA connector is often used for antenna connections on WLAN devices.

SMB connectors

The SMB connector is smaller than the SMA but is used for the same applications as the larger SMA connector.



Item no. 66812

EAN: 4043619668120

Country of origin: Taiwan, Republic of China

Package: Box

Technical details

- Content:
 - 10 x SMA plug for LMR100
 - 10 x SMA plug for LMR200
 - 10 x SMA plug for LMR400
 - 10 x SMA jack for LMR100
 - 10 x SMA jack for LMR200
 - 10 x SMA jack for RG-174
 - 10 x SMB plug for LMR100
 - 10 x SMB jack for LMR100
 - 10 x RP-SMA plug for RG-174
 - 10 x RP-SMA plug for LMR200
 - 10 x RP-SMA jack for RG-174

10 x RP-SMA jack for LMR200

- Housing material: brass gold plated
- Impedance: 50 Ohm
- Frequency range: DC - 8 GHz
- Box dimensions (LxWxH): ca. 265 x 180 x 30 mm

System requirements

- Coaxial cable suitable for crimping

Package content

- 120 x crimping connector

Images



Technical characteristics

Frequency range:	DC - 8 GHz
Impedance:	50 Ohm

Physical characteristics

Housing material:	brass gold plated
-------------------	-------------------

Herstellerinformation

Strasse	Beeskowdamm 13/15
PLZ	14167
Ort	Berlin
Land	Deutschland
E-Mail	info@delock.de
Webseite	www.delock.de