

# Delock USB Condenser Microphone with Stand 24 Bit / 192 kHz for PC and Laptop

## Description

This USB condenser microphone by Delock can be used for high-quality voice and vocal recording, making it suitable for **streaming, podcasting, gaming** and **video meetings**.

### Optimal recordings

The microphone has a **cardioid polar pattern (unidirectional)** and captures the sound ideally. Due to a high performance, low self-noise and precise reproduction, even the finest sounds are optimally recorded.

### High resolution sampling rate

Typical USB microphones work with 16 Bit and 44 kHz. The Delock microphone offers a sampling rate of **24 Bit** and **192 kHz**, so that recordings in **high-resolution HiFi studio quality** are possible.

### Stepless microphone gain

The microphone gain control allows you to individually increase or decrease the volume of the microphone recording.

### Plug & Play

Due to USB Plug & Play the microphone is ready to use immediately, no driver installation is needed. The microphone works with all common operating systems such as **Windows, Mac OS, Chrome OS** and **Linux**.

### Stable & non-slip stand

The metal base with rubber feet ensures that the microphone stands stable on the table. The tripod table stand can be folded and transported easily if required.



## Specification

- Connector: 1 x USB 2.0 Type-B female
- Directivity: unidirectional
- Sensitivity: -13 dB +/- 3 dB
- Frequency range: 20 Hz - 20 kHz
- Sample rate: 24 Bit / 192 kHz
- Signal-to-noise ratio (SNR): ca. 60 dB
- Sound pressure level (SPL): max. 93 dB
- Cable length: ca. 1.5 m
- USB bus powered
- Plug & Play

## System requirements

- Chrome OS
- Linux Kernel 4.4 or above
- Mac OS 10.9 or above
- Windows 8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

## Package content

- USB microphone
- USB 2.0 Type-A to USB 2.0 Type-B cable
- Table stand (tripod)
- Microphone installation ring

## Item no. 66832

EAN: 4043619668328

Country of origin: China

Package: Retail Box

- User manual

## Images



General	
Function:	Plug & Play
Supported operating system:	Chrome OS Linux Kernel 4.4 or above Mac OS 10.9 or above Windows 10 32-bit Windows 10 64-bit Windows 8.1 32-bit Windows 8.1 64-bit
Interface	
connector:	1 x USB 2.0 Type-A male 1 x USB 2.0 Type-B female
Input:	1 x USB 2.0 Type-B female
Technical characteristics	
Frequency range:	20 Hz - 20 kHz
Voltage:	USB bus powered
Sensibility:	- 13 dB +/- 3 dB
Sample rate:	24 Bit / 176 kHz
Signal noise ratio (SNR):	ca. 60 dB
Directivity:	uni-directional
Physical characteristics	
Cable length:	1.5 m
Colour:	black