
Delock Slot bracket SATA 6 Gb/s 7 pin receptacle + Molex 2 pin power plug internal > SATA male pin 8 power external

Description

This slot bracket by Delock allows the external connection of e.g. a SATA DOM memory module with SATA pin 8 power connector to a PC. The power supply is provided by the Molex 2 pin plug.



60 cm / 30 cm

Item no. 84949

EAN: 4043619849499

Country of origin: China

Package: Zip poly bag

Specification

- Connectors:
  1 x SATA 6 Gb/s 7 pin receptacle +
  1 x Molex 2 pin power plug >
  1 x SATA 6 Gb/s plug pin 8 power with latchtype
- E.g. for SATA DOM memories (e.g. for Delock item 54776)
- Data transfer rate up to 6 Gb/s
- Downwards compatible to SATA 1.5 Gb/s and 3 Gb/s
- Voltage: 5 V
- Cable gauge:
  26 AWG data line
  18 AWG power line
- Cable diameter: ca. 2.2 mm
- Cable length without connectors:
  SATA cable: ca. 60 cm
  Molex cable: ca. 30 cm

System requirements

- PC with one free slot
- Power supply with a free Molex power connector
- A free SATA 7 pin plug on the motherboard

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

Package content

- Standard slot bracket
- Low profile slot bracket for exchange

Images



© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

General

Specification:	SATA 6 Gb/s

Interface

Connector 1:	1 x Molex 2 pin male 1 x SATA 6 Gb/s 7 pin receptacle
Connector 2:	1 x SATA 6 Gb/s 8 pin plug

Technical characteristics

Data transfer rate:	6 Gb/s
Voltage:	5 V

Physical characteristics

Conductor gauge:	26 AWG data line 18 AWG power line
Length:	30 cm 60 cm

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.