



Delock Cable DisplayPort 1.2 female > DisplayPort female panel-mount 4K 60 Hz 0.25 m

Description

This cable by Delock can be used to extend an DisplayPort connection and to connect various devices. The female port can be attached with two screws, e.g. to a slot bracket, a cable duct or an enclosure with the corresponding opening. In this way, it is possible to install a DisplayPort connector in an easily accessible position.



Item no. 85113

EAN: 4043619851133 Country of origin: China Package: Zip poly bag

Specification

- Connectors:
 - 1 x DisplayPort 20 pin female >
 - 1 x DisplayPort 20 pin female panel-mount
- DisplayPort 1.2 specification
- Pin 20 is connected (supports 3.3 V)
- Screw type: #4-40 UNC
- Mounting hole: ca. 18 x 7 mm, screw hole pitch ca. 27 mm
- Cable gauge: 30 AWG
- · Cable diameter: ca. 6 mm
- · Gold-plated connectors
- · Transfer of audio and video signals
- Data transfer rate up to 21.6 Gb/s
- Resolution up to 3840 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- · Colour: black
- Length incl. connectors: ca. 25 cm



System requirements

• A free DisplayPort interface

Package content

- DisplayPort panel-mount cable
- 2 screws

Images





General

Interface

| Connector 1: | 1 x DisplayPort 20 pin female panel-mount |
|--------------|-------------------------------------------|
| Connector 2: | 1 x DisplayPort 20 pin female panel-mount |

Technical characteristics

Maximum screen resolution: 3840 x 2160 @ 60 Hz

Physical characteristics

| Conductor gauge: | 30 AWG |
|------------------|--------|
| Length: | 25 cm |
| Colour: | black |