

Delock PoweredUSB cable male 24 V to Mini-DIN 3 pin male 2 m for POS printers and terminals

Description

This PoweredUSB cable by Delock can be used to supply power to a device with Mini-DIN female port via a PC or hub with PoweredUSB 24 V port.



2 m

Item no. 85946

EAN: 4043619859467

Country of origin: China

Package: Zip poly bag

Specification

- Connectors:
 - 1 x PoweredUSB male 24 V >
 - 1 x Hosiden Mini-DIN 3 pin power male
- PoweredUSB specification
- Voltage: 24 V
- Cable gauge: 22 AWG
- Cable diameter: ca. 5 mm
- Cable double shielded
- Colour: black
- Length incl. connectors: ca. 2 m

System requirements

- PC or hub with a free PoweredUSB 24 V female port
- Device with a free Hosiden Mini-DIN 3 pin power female port

Package content

- PoweredUSB cable

Images



General

| | |
|----------------|------------|
| Specification: | PoweredUSB |
|----------------|------------|

Interface

| | |
|--------------|---------------------------------|
| Connector 1: | 1 x PoweredUSB male 24 V |
| Connector 2: | 1 x Hosiden Mini-DIN 3 pin male |

Technical characteristics

| | |
|----------|------|
| Voltage: | 24 V |
|----------|------|

Physical characteristics

| | |
|------------------|--------|
| Conductor gauge: | 22 AWG |
| Shielding: | double |
| Length: | 2 m |
| Colour: | black |