

Delock Passive DisplayPort 1.2 to HDMI Cable 4K 30 Hz 10 m

Description

This cable by Delock enables the connection between devices, e.g. a monitor, with HDMI connector to a DisplayPort interface.



Specification

- Connectors:
 - 1 x DisplayPort male >
 - 1 x HDMI-A male
- Signal direction: DisplayPort input > HDMI output
- Chipset: Parade PS8402A
- DisplayPort 1.2 and High Speed HDMI specification
- Cable gauge: 28 AWG
- Cable diameter: ca. 7.2 mm
- Contacts gold-plated
- Passive cable (level shifter), suitable only for graphics cards with DP++ output
- Transmission of audio and video signals
- Resolution up to 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware)
- Supports 3D displays (1080p @ 120 Hz)
- 2 x ferrite core
- Colour: black
- Dimensions of signal amplifier (LxWxH): ca. 8.00 x 2.20 x 1.35 cm
- Length incl. connectors: ca. 10 m

Item no. 85962

EAN: 4043619859627
 Country of origin: China
 Package: • Zip poly bag

System requirements

- A free DisplayPort female

Package content

- DisplayPort to HDMI cable

Images



| General | |
|----------------------------|------------------------------------|
| Specification: | DisplayPort 1.2 High Speed HDMI |
| Interface | |
| Connector 1: | 1 x DisplayPort male |
| Connector 2: | 1 x HDMI-A male |
| Technical characteristics | |
| Chipset: | Parade PS8402A |
| Maximum screen resolution: | 3840 x 2160 @ 30 Hz |
| Physical characteristics | |
| Ferrite core: | 2 x |
| Pin finishing: | gold-plated |
| Conductor material: | copper |
| Conductor gauge: | 28 AWG |
| Shielding: | triple |
| Diameter: | 7.2 mm |
| Length: | 10 m |
| Colour: | black |