

M12 female 8 pin X-coded field assembly Cat.6A

Description

This industrial connector by Delock can be used to connect various components with M12 connectors, e.g. for machine control or automation.



Item no. 86056

EAN: 4043619860562

Country of origin: Taiwan,
Republic of China

Package: Zip poly bag

Technical details

- Connectors:
 - 1 x M12 female X-coded 8 pin
 - 1 x LSA block
- Compliant with Cat.6A requirements of ISO/IEC 11801 Edition 2.2, EN 50173-1 and IEC 61076-2-109, and ANSI/TIA 568-D.2
- Supports IEEE 802.3an: 10GBASE-T
- Supports PoE++
- Material: zinc diecast
- For solid or stranded wire up to 0.644 mm (22 - 26 AWG)
- For cable diameter from 5.5 - 9.0 mm
- Operating temperature: -40 °C ~ 85 °C
- Protection class: IP67
- Dimensions (LxD): ca. 48.5 x 20.1 mm


System requirements

- 16 mm spanner for assembly

Package content

- Connector
- Installation manual

Images



Interface

Connector 1:	1 x M12 female X-coded 8 pin
Connector 2:	1 x LSA (toolfree)

Physical characteristics

Housing material:	zinc die cast
Pin finishing:	gold-plated
Diameter:	20 mm
Length:	48 mm

Manufacturer information

Street Beeskowdamm 13/15
 Postal code 14167
 City Berlin
 Country Deutschland
 E-Mail info@delock.de
 Website www.delock.de

