

# Delock Media Converter 10/100/1000Base-T to SFP compact

## Description

This Delock Gigabit Ethernet Media Converter can be used to expand your network by an optical fiber interface. In the SFP slot, an optional 100 Mb/s or 1 Gb/s SFP module can be used. The compact dimensions allow a space-saving installation.



## Specification

- Connector:
  - SFP slot for 100 Mb/s or 1 Gb/s SFP modules (Dual rate) (SFP module not included)
  - RJ45 connector for 10/100/1000Base-T
- Transmission rate up to 1 Gb/s
- 5 LEDs for status monitoring
- DIP-switch for configuration of LFP (Link Fault Pass Through), Half- or Full-Duplex, 10/100/1000 Mb/s mode
- Power supply with 3.3 V included
- Operating temperature: 0° ~ 50° C
- Storage temperature: - 20° ~ 60° C
- Relative humidity: 5 ~ 90 % (not condensing)
- Robust metal housing
- Power consumption: 2.3 W
- Dimensions (LxWxH): ca. 74 x 51 x 20 mm

## Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.2 A
- Output: 3.3 V / 1.5 A
- Ground outside, plus inside
- Dimensions:
  - inside: ø ca.0.75 mm
  - outside: ø ca. 2.4 mm
  - length: ca. 8.2 mm

## System requirements

- Device with one free RJ45 port

## Package content

- Media Converter
- Power supply
- User manual

## Item no. 86440

EAN: 4043619864409

Country of origin: Taiwan, Republic of China

Package: • White Box

Images

