

Delock Media Converter 100Base-FX SC SM 1310 nm 30 km compact

Description

This Delock Fast Ethernet Media Converter can be used to expand a network with an optical fiber interface. The compact dimensions allow a space-saving installation.



Item no. 86443

EAN: 4043619864430

Country of origin: Taiwan,
Republic of China

Package: White Box

Specification

- Connector:
SC Duplex connector for 100Base-FX
RJ45 connector for 10/100Base-T
- For Single-Mode-Fiber, 1310 nm wavelength
- Distance up to 30 km with 9/125 µm fiber
- Transmission rate up to 100 Mb/s
- 5 LEDs for status monitoring
- DIP-switch for configuration of LFP (Link Fault Pass Through),
Half- or Full-Duplex, 10/100 Mb/s mode
- Power supply with 3.3 V included
- Operating temperature: 0° ~ 50° C
- Storage temperature: - 20° ~ 60° C
- Relative humidity: 5 ~ 90 % (not condensing)
- Robust metal housing
- Power consumption: 1.9 W
- Dimensions (LxWxH): ca. 74 x 51 x 20 mm

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.5 A
- Output: 3.3 V / 2.0 A
- Ground outside, plus inside
- Dimensions:
 - inside: ø ca.0.75 mm
 - outside: ø ca. 2.4 mm
 - length: ca. 8.2 mm

System requirements

- Device with one free RJ45 port

Package content

- Media Converter
- Power supply
- User manual

Images

