

# Delock Docking Station for MacBook with 4K and PD 3.0

## Description

The docking station by Delock is the mobile companion for MacBook with USB Type-C™ connection. Up to **2 USB devices** can be connected to the docking station. Due to its size and the specially arranged USB-C™ connector, the docking station connects perfectly to the MacBook.

### Integrated Card Reader

In addition, the docking station with integrated card reader expands a PC or laptop by an **SD** and a **Micro SD** slot via the USB Type-C™ connection.

### USB Power Delivery (USB PD 3.0) support up to 100 watt

The docking station has a USB Type-C™ Power Delivery port to connect the power supply of the laptop or tablet to charge it. In addition it also supplies the USB Type-A female with power. The docking station can also be used without a power supply.

### Small sturdy helper

Due to its small dimensions and its **sturdy housing**, this Delock Hub is particularly suitable for travelling. It can simply be packed into the bag together with the laptop or tablet and used as needed. If the USB-C™ plug is inserted during transport, it cannot be polluted or damaged.



## Specification

- Connectors:
  - 1 x SuperSpeed USB (USB 3.2 Gen 1) USB Type-C™ male >
  - 1 x SuperSpeed USB (USB 3.2 Gen 1) Type-A female
  - 1 x HDMI-A female
  - 1 x SD slot
  - 1 x Micro SD slot
  - 1 x SuperSpeed USB (USB 3.2 Gen 1) USB Type-C™ Power Delivery female
- Chipset: Fresco Logic FL5001, FL7102, Norelsys NS1081C
- Slide switch for USB-C™ male
- Resolution up to 3840 x 2160 @ 30 Hz  
(depending on the system and the connected hardware)
- Transmission of audio and video signals
- Data transfer rate up to:
  - SuperSpeed USB 5 Gbps,
  - Hi-Speed 480 Mbps,
  - Full-Speed 12 Mbps,
  - Low-Speed 1.5 Mbps
- It can only be used one memory card, not both at the same time
- The Card Reader supports following memory cards:
  1. Slot Secure Digital  
SD, SD3.0 UHS-I, SD High Capacity (SDHC), SD Ultra, SDHC Ultra, SDXC, MMC-I, MMC-II, MMC 4.0, Mini SD, Mini SDHC, MMCmobile, RS-MMC, RS-MMC 4.0
  2. Slot Micro Secure Digital  
Micro SD, Micro SDHC, Micro SDHC Ultra, T-Flash, MMCmicro
- USB Power Delivery (PD) 3.0
- Metal housing
- Dimensions (LxWxH): ca. 113 x 35 x 10 mm
- Plug & Play

## System requirements

- Mac OS 10.14.5 or above
- Laptop or tablet with a free USB Type-C™ or Thunderbolt™ 3 port

## Item no. 87745

EAN: 4043619877454

Country of origin: China

Package: • Retail Box



### Package content

- Docking station
- User manual

### Images



General	
Supported operating system:	Mac OS 10.14.5 or above
Interface	
Connector 1:	1 x SuperSpeed USB (USB 3.2 Gen 1) USB Type-C™ male
Connector 2:	1 x SuperSpeed USB (USB 3.2 Gen 1) Type-A female
connector 3:	1 x SuperSpeed USB (USB 3.2 Gen 1) USB Type-C™ Power Delivery female
connector 4:	1 x Micro SD slot
connector 5:	1 x SD slot
Output:	1 x HDMI-A 19 pin female
Technical characteristics	
Chipset:	Fresco Logic FL7102 Norelsys NS1081C Fresco Logic FL5001
Data transfer rate:	5 Gbps