

Delock USB Type-C™ 3.2 Dockingstation 4K HDMI DP / 1080p VGA, USB Hub und PD 3.0

Description

This docking station by Delock can be connected to a computer with a USB-C™ Alt-Mode or Thunderbolt™ 3 port and provides a variety of interfaces. **Three monitors can be operated simultaneously** at the DisplayPort, HDMI and VGA outputs. Two built-in USB Type-A ports and one USB Type-C™ port allows the use of peripherals.

Multi-Stream Transport (MST)

The product is an MST hub and supports the extended desktop configuration of DisplayPort. This allows **multiple monitors to be combined into one large display**. The maximum resolution for simultaneous playback on two or three monitors depends on the system and connected hardware.

When Mac OS is used, the same image is displayed on all ports (mirrored), it is not possible to use the video ports independently of each other.

USB Power Delivery (USB PD 3.0) support up to 100 watt

The docking station has a USB Type-C™ Power Delivery port to connect the power supply of the laptop or tablet to charge it. The docking station can also be used without a power supply.



Item no. 87773

EAN: 4043619877737

Country of origin: China

Package: Retail Box

Specification

- Connectors:
 - 1 x HDMI-A female
 - 1 x DisplayPort female
 - 1 x VGA female
 - 1 x USB Type-C™ PD female (power supply)
 - 1 x USB Type-C™ female (data transfer)
 - 1 x USB Type-C™ female (connection to host)
 - 2 x SuperSpeed USB (USB 3.2 Gen 1) Type-A female
- Chipset: VMM3332, VL103R, VL817, VL170
- Maximum resolution (depending on the system and the connected hardware):

Single Display	HDMI: 3840 x 2160 @ 30 Hz DP: 3840 x 2160 @ 30 Hz VGA : 1920 x 1080 @ 60 Hz
Dual Display MST	HDMI + DP: 1920 x 1080 @ 60 Hz

	HDMI + VGA: 1920 x 1080 @ 60 Hz DP + VGA: 1920 x 1080 @ 60 Hz
Dual Display Mac	HDMI + DP: 3840 x 2160 @ 30 Hz HDMI + VGA: 1920 x 1080 @ 60 Hz DP + VGA: 1920 x 1080 @ 60 Hz
Triple Display MST	HDMI + DP + VGA: 1280 x 720p @ 60 Hz
Triple Display Mac	HDMI + DP + VGA: 1920 x 1080 @ 30 Hz

- Transmission of audio and video signals
- Setting: extended, mirrored, primary display
- Output power: 4.5 W per port
- Input power: 1 x USB Type-C™ female max. 100 W
- Colour: black
- Dimensions (LxWxH): ca. 127 x 63 x 14 mm

System requirements

- Android 9.0 or above
- Chrome OS 78.0 or above
- Mac OS 10.15.3 or above
- Windows 8.1/8.1-64/10/10-64/11
- Device with a free USB Type-C™ port and DisplayPort alternate mode or with a free Thunderbolt™ 3 port

Package content

- USB-C™ docking station
- Cable USB-C™ male to USB-C™ male, length ca. 10 cm
- User manual

Images



General

Supported operating system:	Android 9.0 or above Chrome OS 78.0 or above Mac OS 10.15.3 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit
-----------------------------	--

Interface

Output:	1 x USB 5 Gbps USB Type-C™ female 1 x DisplayPort female 1 x HDMI-A female 1 x VGA female 2 x USB 5 Gbps Type-A female
Input:	1 x USB Type-C™ female (power supply) 1 x USB Type-C™ female

Technical characteristics

Maximum screen resolution:	3840 x 2160 @ 30 Hz
----------------------------	---------------------