

# Delock USB 40 Gbps USB Type-C™ Docking Station 8K - HDMI / USB 10 Gbps / 2.5 Gigabit LAN / PD 3.0 100 W

## Description

This docking station by Delock can be connected to a computer with a USB-C™ DP Alt Mode or Thunderbolt™ 3 or Thunderbolt™ 4 port and provides a variety of interfaces. A monitor can be operated at the HDMI output port by a maximum resolution up to **8K Ultra HD** (7680 x 4320 @ 60 Hz). **Two built-in USB Type-A and one USB-C™ port** allow the use of peripherals.



## Integrated 10/100/1000/2500 Mbps LAN interface

In addition, the docking station with integrated **RJ45 2.5 Gigabit LAN** connection expands a PC or laptop by a network interface.

## USB Power Delivery (USB PD 3.0) support up to 85 watt

The docking station has a **USB Type-C™ Power Delivery port**. If this port is connected to the power supply of the laptop or tablet, the host device is charged with up to 85 watts during operation.

## Small sturdy helper

Due to its **small dimensions and its sturdy housing**, this Delock docking station is particularly suitable for travelling. It can simply be packed into the bag together with the laptop or tablet and used as needed.

## Item no. 87865

EAN: 4043619878659

Country of origin: China

Package: Retail Box

## Specification

- Connectors:
  - 1 x USB 40 Gbps USB Type-C™ male
  - 2 x USB 10 Gbps Type-A female
  - 1 x USB 10 Gbps USB Type-C™ female
  - 1 x HDMI female
  - 1 x 2.5 Gigabit LAN RJ45 jack
  - 1 x USB Type-C™ PD female (power supply)

- Maximum resolution (depending on the system and the connected hardware):  
with DSC: 7680 x 4320 @ 60 Hz  
without DSC: 7680 x 4320 @ 30 Hz
- Transmission of audio and video signals
- Supports HDCP 1.4 and 2.2
- Supports HDR
- Input power PD port: 100 W, 15 W are used for the docking station
- Output power for host: max. 85 W
- Metal housing
- Cable length without connectors: ca. 25 cm
- Colour: grey
- Dimensions (LxWxH): ca. 142 x 30 x 18 mm

## System requirements

- Linux Kernel 5.15 or above
- Mac OS 12.4 or above
- Windows 8.1/8.1-64/10/10-64/11
- iPad Air (4th Generation) or above
- iPad Pro (3rd Generation) or above
- Surface Pro 7
- Device with a free USB Type-C™ port and DisplayPort alternate mode or with a free Thunderbolt™ 3 or Thunderbolt™ 4 port

## Package content

- USB 40 Gbps docking station
- User manual

## Images



## General

Supported operating system:	Surface Pro 7 Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit iPad Pro (3rd Generation) or above iPad Air (4th Generation) or above Windows 11 Mac OS 12.4 oder höher Linux Kernel 5.15 or above
-----------------------------	---

## Interface

Connector 1:	1 x USB 40 Gbps USB Type-C™ male
Connector 2:	1 x HDMI female
connector 3:	2 x USB 10 Gbps Type-A female
connector 4:	1 x 2.5 Gigabit LAN RJ45 jack

## Technical characteristics

Maximum screen resolution:	7680 x 4320 @ 60 Hz
----------------------------	---------------------

## Physical characteristics

Housing material:	metal / plastic
Cable length:	25 cm
Colour:	grey