


Delock PCI Express x1 kartica na 1 x RJ45 2,5 Gigabit LAN

Opis

Delock PCI Express kartica sadrži dva mrežna priključka brzine prijenosa podataka do 2500 Mbps.

NBASE-T za veću brzinu

Suvremene usluge i nove tehnologije zahtijevaju veće pojasne širine. NBASE-T tehnologija omogućava brzine od 1 Gbps i 2,5 Gbps s konvencionalnim radnim mrežnim kabelima. Idealni prijenos postavlja se automatski.



Predmet br. 88100

EAN: 4043619881000

Zemlja podrijetla: China

Pakiranje: Retail Box

Tehnički podaci

- Priključak:
vanjski: 1 x 2,5 Gigabit LAN RJ45 ženski
unutarnji: 1 x PCI Express x1, V2.1
- Skup čipova: Realtek RTL8125B
- Brzina prijenosa podataka:
Ethernet do 10 Mbps
Fast Ethernet do 100 Mbps
Gigabit Ethernet do 1000 Mbps
NBASE-T s brzinom do 2,5 Gbps
PCI Express x1 do 2,5 Gbps
- Podržava IEEE 802.3 / 802.3u / 802.3ab
- Podržava buđenje na LAN (WOL)
- Podržava prioritet kodiranja IEEE 802.1P 2. sloja
- Podržava kontrolu protoka IEEE 802.3x puni dupleks
- Podržava IEEE 802.1Q virtualni LAN (VLAN)
- Podržava 16k Jumbo okvire
- Podržava PXE
- LED indikator povezivanja i šupljine

Preduvjeti sustava

- Linux Kernel 3.2 ili noviji
- Windows 10/10-64/11
- Računalo s jednim slobodnim PCI Express utorom

Sadržaj pakiranja

- PCI Express kartica
- Nosač niskog profila
- Korisnički priručnik

Slike



General

Supported operating system:	Linux Kernel 3.2 ili noviji Windows 10 32-bit Windows 10 64-bit Windows 11
LED indikator:	Link and activity

Interface

Vanjski:	1 x Gigabit LAN RJ45 jack
Unutarnji:	1 x PCI Express x1, V2.1

Technical characteristics

Skup čipova:	Realtek RTL8125B
Brzina prijenosa podataka:	Fast Ethernet up to 100 Mbps Gigabit Ethernet up to 1 Gbps Gigabit Ethernet up to 2.5 Gbps

Physical characteristics

Slot bracket:	niskoprofilni standard
---------------	---------------------------