

Delock WLAN 802.11 ac/a/h/b/g/n Antenna RP-SMA Quick 6 ~ 8 dBi Directional Joint

Description

This wireless LAN antenna can be connected to your device with RP-SMA interface, in order to send and receive signals. With the help of the variable inclination of the antenna tilt and the magnetic base, you can position the antenna individually.



Item no. 88903

EAN: 4043619889037

Country of origin: Taiwan,
Republic of China

Package: Poly bag

Specification

- RP-SMA plug quick
- With flexible joint, rotatable
- Frequency range: 2.400 ~ 2.500 GHz, 5.150 ~ 5.875 GHz
- Peak gain: 6 dBi, 8 dBi
- VSWR: 2.0 : 1 max.
- HPBW: h/v: 70°/70°, h/v: 50°/60°
- Polarisation: linear, vertical
- Impedance: 50 Ohm
- Body: ABS UV resistant
- Operating temperature: -10°C ~ 55°C
- Cable length: 1 m
- Cable type: ULA 100
- Cable attenuation: 1.40 dB@2.500 GHz
2.30 dB@5.875 GHz
- Cable colour: black
- Dimension: 123.00 x 69.00 x 29.50 mm
- Weight: 122 g

Package content

- Antenna

Images

