

Delock WLAN 802.11 ac/a/b/g/n Antenna SMA plug 2 dBi omnidirectional with tilt joint black

Description

This Wireless LAN antenna can be connected to a WLAN device with SMA interface, in order to send and receive signals.

Bluetooth



Item no. 89437

EAN: 4043619894376

Country of origin: Taiwan,
Republic of China

Package: Retail Box

Specification

- Connector: SMA plug
- Frequency range:
2.400 - 2.500 GHz
5.150 - 5.875 GHz
- Antenna gain: 2 dBi
- Impedance: 50 Ohm
- Polarisation: linear, vertical
- VSWR: 2.0
- Operating temperature: -10 °C ~ 55 °C
- Housing material: ABS
- Colour: black
- Length:
ca. 111.70 mm (with tilt joint)
ca. 83.40 mm (without tilt joint)
- Diameter:
ca. 7.80 mm (top)
ca. 10.00 mm (SMA)




System requirements

- Device with a free SMA jack

Package content

- WLAN antenna

Images



Interface

connector:	SMA Stecker
------------	-------------

Technical characteristics

Frequency range:	2.400 - 2.500 GHz 5.150 - 5.875 GHz
Gain:	2 dBi
Impedance:	50 Ω
Operating temperature:	-10 °C ~ 55 °C
Polarisation:	linear vertical
VSWR:	2.0

Physical characteristics

Housing material:	ABS
Diameter connector:	10.00 mm
Length with tilt joint:	111.70 mm
Length without tilt joint:	83.40 mm
Colour:	black