
Delock PCI Express x4 Card > 2 x external USB 3.1 Gen 2 Type-A female

Description

This PCI Express card by Delock expands the PC by two external USB 3.1 ports. Different USB Type-A devices, such as docking stations, card readers, external housings etc., can be connected to the card.



Item no. 89554

EAN: 4043619895540

Country of origin: China

Package: Retail Box

Specification

- Connector:
  external:
  2 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) Type-A female
  internal:
  1 x SATA 15 pin power connector
  1 x PCI Express x4, V2.0
- Chipset: Asmedia ASM1142
- Data transfer rate up to:
  SuperSpeed USB 10 Gbps,
  SuperSpeed USB 5 Gbps,
  Hi-Speed 480 Mbps,
  Full-Speed 12 Mbps,
  Low-Speed 1.5 Mbps
- Power supply via PCI Express interface or via SATA 15 pin power connector
- Electrical power per port: max. 4.5 watt (5 V / 900 mA)
- Supports eXtensible Host Controller Interface (xHCI) specifications 1.1
- Supports UASP

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 4.6
- PC with one free PCI Express x4 / x8 / x16 / x32 slot

Package content

- PCI Express card SuperSpeed USB 10 Gbps
- Low profile bracket
- Driver CD
- User manual

Images







© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

General

Supported operating system:	Linux Kernel 4.6 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit

Interface

External:	2 x USB 10 Gbps Type-A female
Internal:	1 x PCI Express x4, V2.0 1 x SATA 15 pin plug

Technical characteristics

Chipset:	Asmedia ASM1142
Data transfer rate:	USB 10 Gbps up to 10 Gb/s

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.