

Delock PCI Express Card > 2 x Gigabit LAN PoE+ RJ45

Descrizione

This PCI Express card by IOI offers two network ports with a data transfer rate up to 1 Gbps. The RJ45 ports support Power over Ethernet according to IEEE 802.3af / 802.3at, so you can supply power to PoE-enabled devices, such as an IP camera or a PoE splitter via the network cable.



Articolo n. 89560

EAN: 4043619895601

Paese di origine: Taiwan,
Republic of China

Pacchetto: White Box

Specifiche

- IOI item number: GEPX2-PCIE1XG201L
- Connector:
 - external:
 - 2 x Gigabit LAN RJ45 jack with screw nuts
 - internal:
 - 1 x SATA 15 pin power connector
 - 1 x PCI Express x1, V2.0
- Chipset: Renesas
- Data transfer rate:
 - Ethernet up to 10 Mb/s
 - Fast Ethernet up to 100 Mb/s
 - Gigabit Ethernet up to 1 Gbps
 - PCI Express x1 up to 5 Gbps
- Supports Full Duplex flow control (IEEE 802.3x)
- Supports IEEE 802.3 10Base-T and 802.3u 100Base-TX
- Supports IEEE 802.1P Layer 2 Priority Encoding
- Supports IEEE 802.1Q VLAN tagging
- Supports IEEE 802.3az-2010 (EEE)
- Supports 9k Jumbo frames

- Supports IEEE 802.3af & IEEE 802.3at Power Sourcing Equipment (PSE)
- Power delivery: max. 30 W total
- PoE power input from PCIe or SATA 15 pin power connector

Requisiti di sistema

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux Kernel 2.6.31
- PC with one free PCI Express x4 / x8 / x16 / x32 slot

Contenuto della confezione

- PCI Express card
- Low profile bracket
- Driver CD
- User manual

Immagini



General

Supported operating system:	Linux Kernel 2.6.31 Windows 10 32-bit Windows 10 64-bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit
-----------------------------	---

Interface

External:	2 x RJ45 femmina
Internal:	1 x SATA a 15 pin maschio 1 x PCI Express x1, V2.0

Technical characteristics

Data transfer rate:	Ethernet up to 10 Mbps Fast Ethernet up to 100 Mbps Gigabit Ethernet up to 1 Gbps PCI Express up to 5 Gb/s
---------------------	---

Physical characteristics

Slot bracket:	basso profilo standard
---------------	---------------------------