


# Delock PCI Express x1 Card 1 x RJ45 2.5 Gigabit LAN RTL8125

## Description

The PCI Express card by Delock offers one network port with a data transfer rate up to 2500 Mbps.

### NBASE-T for higher speed

Modern services and new technologies require higher bandwidths. NBASE-T technology enables speeds of 1 Gbps and 2.5 Gbps with conventional networking cables. The best possible transmission rate is set automatically.



**Item no. 89564**

EAN: 4043619895649

Country of origin: China

Package: Retail Box

## Specification

- Connectors:  
external: 1 x 2.5 Gigabit LAN RJ45 jack  
internal: 1 x PCI Express x1, V2.1
- Chipset: Realtek RTL8125B
- Data transfer rate:  
Ethernet up to 10 Mbps (Half/Full Duplex)  
Fast Ethernet up to 100 Mbps (Half/Full Duplex)  
Gigabit Ethernet up to 1000 Mbps (Half/Full Duplex)  
NBASE-T with up to 2.5 Gbps (Half/Full Duplex)  
PCI Express x1 up to 2.5 Gbps
- Compatible with IEEE 802.3, IEEE 802.3u, IEEE 802.3ab
- Supports Wake On LAN (WOL)
- Supports IEEE 802.1P layer 2 priority encoding
- Supports IEEE 802.3x full duplex flow control
- Supports IEEE 802.1Q Virtual LAN (VLAN)
- Supports 9k Jumbo Frames
- LED indicator for link and activity

---

## System requirements

- Windows 8.1/8.1-64/10/10-64
- PC with one free PCI Express slot

---

## Package content

- PCI Express card
- Low profile bracket
- Driver CD
- User manual

---

## Images



## General

Supported operating system:	Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit
-----------------------------	------------------------------------------------------------------------------------

## Interface

External:	1 x Gigabit LAN RJ45 jack
Internal:	1 x PCI Express x1, V2.1

## Technical characteristics

Chipset:	Realtek RTL8125B
Data transfer rate:	Ethernet up to 10 Mbps Fast Ethernet up to 100 Mbps Gigabit Ethernet up to 1 Gbps Gigabit Ethernet up to 2.5 Gbps
Operating temperature:	5 °C ~ 50 °C

## Physical characteristics

Slot bracket:	Low Profile standard
---------------	-------------------------