

# Delock PCI Express x1 Card to 1 x Serial RS-232

## Description

The Delock PCI Express card expands a PC by one external serial port. Different devices such as scanner, printer, mouse etc. can be connected to this card. By using the included low profile bracket, the PCI Expresscard can be also installed into a Mini-PC.



**Item no. 90000**

EAN: 4043619900008

Country of origin: China

Package: Retail Box

## Specification

- Connectors:
  - external: 1 x serial RS-232 DB9 male
  - internal: 1 x PCI Express x1, V2.0
- Chipset: Exar XR17V352
- Data transfer rate up to 230.4 Kbps
- FIFO: 256 byte
- Compatible with 16C550 UART
- Databits: 5, 6, 7, 8
- Stop bits: 1, 1.5, 2
- Parity: even, odd, none, mark, space
- Flow control: none, hardware RTS / CTS, software XON / XOFF
- Dimensions (LxW): ca. 64 x 45 mm

## System requirements

- Windows 8.1/8.1-64/10/10-64/11
- PC with one free PCI Express slot

---

## Package content

- PCI Express card
- Low profile bracket
- Driver CD
- User manual

---

## Images



## General

Form factor:	Low Profile (MD1)
Specification:	RS-232 (EIA / TIA) PCI Express 2.0
Supported operating system:	Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows 11
Slot:	PCIe

## Interface

Connector 1:	1 x PCI Express x1
Connector 2:	1 x Serial RS-232 DB9 male

## Technical characteristics

Chipset:	Exar 17V352
Data transfer rate:	up to 230.4 Kb/s
FIFO:	1 x 256 Byte
Signal transmission:	TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
Data transmission:	asynchronous Bi-directional Half duplex full duplex
UART:	16C550
Data bits:	5, 6, 7, 8

## Physical characteristics

Screw type:	#4-40 UNC
Slot bracket:	Low Profile standard

Width:	45 mm
Height:	64 mm
Colour:	black