

# Delock PCI Express x4 Card to 1 x SuperSpeed USB 20 Gbps (USB 3.2 Gen 2x2) USB Type-C™ + 1 x USB Type-C™ PD 20 Watt

## Description

This PCI Express card by Delock expands the PC by one external **USB 3.2** port. Different USB devices, such as docking stations, card readers, external enclosures etc., can be connected to the card.

### SuperSpeed USB 20 Gbps

The card allows a data transfer rate of 20 Gbps on the USB-C™ port.

### Power Delivery (PD) at the USB-C™ port

The USB Type-C™ port supports the Power Delivery function as well as diverse fast charging technologies. This allows connected devices such as smartphones, tablets and even laptops to be charged.



**Item no. 90074**

EAN: 4043619900749

Country of origin: China

Package: Retail Box

## Specification

- Connectors:  
external:  
1 x SuperSpeed USB 20 Gbps (USB 3.2 Gen 2x2) USB Type-C™ female  
1 x USB Type-C™ Power Delivery female  
internal:  
1 x PCI Express x4, V3.0  
1 x SATA 15 pin power connector
- Chipset: Asmedia ASM3242
- Data transfer rate up to:  
SuperSpeed USB 20 Gbps,  
SuperSpeed USB 10 Gbps,  
SuperSpeed USB 5 Gbps,  
Hi-Speed 480 Mbps,  
Full-Speed 12 Mbps,  
Low-Speed 1.5 Mbps
- Downwards compatible to USB 3.0, USB 2.0, USB 1.1
- Electrical power data port: max. 15 watt (5 V / 3 A)

- Electrical power PD port: max. 20 watt (5 ~ 12 V)
- Bootable
- Supports UASP
- Supports eXtensible Host Controller Interface (xHCI) specification 1.1
- Supports Multiple INs

---

## System requirements

- Linux Kernel 5.8 or above
- Windows 8.1/8.1-64/10/10-64
- PC with one free PCI Express x4 / x8 / x16 / x32 slot

---

## Package content

- PCI Express card SuperSpeed USB 20 Gbps
- Low profile bracket
- User manual

---

## Images



## General

Form factor:	Low Profile
Function:	bootable
Supported operating system:	Linux Kernel 5.8.0 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit

## Interface

External:	1 x USB 20 Gbps USB Type-C™ female 1 x USB Type-C™ Power Delivery female
-----------	---

## Technical characteristics

Chipset:	Asmedia ASM3242
Data transfer rate:	20 Gbps