

Delock Serial Barcode scanner 2D fixed mount - Image scanner

Beskrivning

This wired serial barcode scanner by Delock can be connected to a device with a free RS-232 interface. With this Image scanner with CMOS image sensor, all common 1D and 2D barcode types can be detected without using any scan button. Furthermore, this fixed mount barcode scanner is able to read barcodes shown on displays and monitors.

Even in a completely dark environment, the scanner turns on automatically, when an object appears in its scanning area. There is an additional red LED on top of the scanner indicating the readiness of the scanner for operation and a green LED confirming a positive scan.

Depending on your specific requirement, various visual and acoustic signals can be configured and the scan process also be triggered by the appropriate software.

The resistant housing protects the scanner from external mechanical influences and prevents the limited ingress of dust and low pressure water jets. With the included mounting brackets, the scanner can be installed variable in different alignments.



Artikelnummer 90287

EAN: 4043619902873

Ursprungsland: Taiwan,
Republic of China

Paket: White Box

Specifikationer

- Connectors:
 - 1 x Serial RS-232 DB9 female with screws
 - 1 x 5 V DC jack
- Resolution:
 - Code 39: 0.127 mm
 - QR Code: 0.169 mm
- Trigger: automatic, software
- Reading distance: ca. 45 mm bis 285 mm
- Light source: LED, 625 nm
- Light colour: visible LED red
- Aimer: Laser Class 1, 650 nm, red
- Sensor: CMOS image sensor
- Scan rate: up to 60 frames per second

- Scan angle:
horizontal: 36°
vertical: 23°
- Surrounding brightness: max. 30000 Lux
- Input voltage: 5 V
- Power supply via pin 9 on the RS-232 port or via DC jack
- Current consumption:
operation: max. 320 mA
standby: max. 100 mA
- Operating temperature: -10 °C ~ 55 °C
- Storage temperature: -20 °C ~ 65 °C
- Relative humidity: 0 - 95 % (non condensing)
- Protection class: IP55
- Colour: black
- Weight:
Barcode scanner: ca. 85 g
Mounting brackets: ca. 15 g
- Dimensions (LxWxH): ca. 56 x 41 x 20 mm
- Cable length: ca. 85.9 cm
- Software:
EzUtility Software (standard mode/automatic Trigger)
BEO Software (command mode/software Trigger)
- Scancodes:
1D Codes:
UPC-A / UPC-E
EAN-8 / EAN-13
Matrix 2 of 5
China Postal Code (Toshiba Code)
Industrial 2 of 5
Interleaved 2 of 5
Codabar
Code 11
Code 32
Standard Code 39
Full ASCII Code 39
Code 93
Code 128
EAN / UCC 128
MSI Plessey Code
UK Plessey Code
Telepen Code
GS1 Databar
IATA Code

2D Codes:
PDF417
DataMatrix
QR Code
Micro QR Code
Chinese Sensible Code

Specifikation för strömanslutning

- Ground outside, plus inside
- Dimensions:
inside: $\varnothing$ ca. 2.1 mm
outside: $\varnothing$ ca. 5.5 mm
length: ca. 12.5 mm




Systemkrav

- Windows 7/7-32/8.1/8.1-64/10/10-64
- Device with RS-232 interface

Paketets innehåll

- Barcode scanner
- 1 x mounting bracket 90°
- 1 x mounting bracket 60°
- 2 x screw
- User manual
- Gender Changer

Bilder



Interface

kontakt:	1 x seriell RS-232 DB9 hona med skruvar
----------	---

Technical characteristics

Operating voltage:	5 V
Driftstemperatur:	-10 °C ~ 55 °C
Current consumption:	användning 320 mA viloläge: 100 mA
Upplösning:	0,127 mm 0,169 mm
Avläsningshastighet:	60 bilder per sekund
Avtryckare:	automatisk programvara
Läsavstånd:	45 mm - 285 mm
Ljuskälla:	LED, 625 nm
Sensor:	CMOS Bildsensor

Scancodes:	UPC-A UPC-E EAN-8 EAN-13 Matrix 2 of 5 China Postal Code (Toshiba Code) Industrial 2 of 5 Interleaved 2 of 5 Codabar Code 11 Code 32 Standard Code 39 Full ASCII Code 39 Code 93 Code 128 MSI Plessey Code UK Plessey Code Telepen Code GS1 Databar IATA Code EAN / UCC 128 PDF417 DataMatrix QR Code Micro QR Code Chinese Sensible Code
Omgivningens ljus:	30000 Lux

Physical characteristics

Weight:	85 g
Cable length incl. connector:	86 cm
Längd:	56 mm
Width:	41 mm
Height:	20 mm
Färg:	svart