

Delock PCI Express x16 Card to 1 x NVMe M.2 Key M

Description

This PCI Express card by Delock expands the PC by one M.2 slot. One M.2 module in 2280, 2260, 2242 or 2230 format can be connected. If the card will be installed in the PC, the slot bracket does not have to be removed.



Specification

- Connectors:
 - 1 x 67 pin M.2 key M slot
 - 1 x PCI Express x16 (4-Lane), V4.0
- Interface: PCIe
- Supports M.2 modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based on PCIe
- Bootable, ex UEFI version 2.3.1
- Supports NVM Express (NVMe)
- 1 x LED indicator
- Holes in the PCB for cooling the SSD
- Holder for lock on PCI Express x16 slots
- Dimensions (LxWxH) without PCIe connector and lock holder: ca. 98 x 32 x 5 mm

Item no. 90300

EAN: 4043619903009

Country of origin: China

Package: Retail Box



System requirements

- Linux Kernel 3.17 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC with one free PCI Express x16 / x32 slot

Package content

- PCI Express card
- 1 x fixing screw for M.2 module
- Screwdriver
- User manual

Images



General	
Function:	NVM Express (NVMe)
Supported operating system:	Linux Kernel 3.17 or above Windows 10 32-bit Windows 10 64-bit Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit
Slot:	PCIe
Supported module:	M.2 modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based on PCIe
Interface	
Internal:	1 x 67 pin M.2 key M slot 1 x PCI Express x16, V4.0