


# **Delock PCI Express Card to 1 x Parallel IEEE1284**

#### Description

This PCI Express card by Delock expands a PC by one external parallel port. Different devices such as scanner, printer etc. can be connected to this card.



Item no. 90412

EAN: 4043619904129 Country of origin: China Package: Retail Box

#### Specification

- Connectors: external: 1 x Parallel DB25 female internal: 1 x PCI Express x1, V1.1
- Chipset: WCH382L
- Data transfer rate up to 1.5 Mbps
- FIFO: 256 byte
- SPP, EPP, ECP compatible to IEEE 1284
- Operating temperature: -40 °C ~ 85 °C
- Relative humidity: 0 95 % (non condensing)
- Dimensions (LxWxH): ca. 79 x 59 x 13 mm

#### System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64/11
- Windows Server 2008 R2/Server 2012/Server 2012 R2/Server 2016
- PC with one free PCI Express slot

### Package content

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.





- PCI Express card
- Low profile bracket
- Driver CD
- User manual

#### Images





#### General

Form factor:	Low Profile
Specification:	IEEE1284 PCIe 1.1 SPP, EPP, ECP
Supported operating system:	Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit
Slot:	PCIe

#### Interface

External:	1 x Parallel DB25 female
Internal:	1 x PCI Express x1, V1.1

## **Technical characteristics**

Chipset:	WCH CH382L
Data transfer rate:	1.5 MBps LPT
Data transmission:	Bi-directional

## **Physical characteristics**

Slot bracket:	Low Profile standard
Length:	79 mm
Width:	59 mm
Height:	13 mm