


Delock PCI Express x1 Card 1 x RJ45 2.5 Gigabit LAN RTL8125

Description

The PCI Express card by Delock offers one network port with a data transfer rate up to 2500 Mbps.

NBASE-T for higher speed

Modern services and new technologies require higher bandwidths. NBASE-T technology enables speeds of 1 Gbps and 2.5 Gbps with conventional networking cables. The best possible transmission rate is set automatically.



Item no. 90440

EAN: 4043619904402 Country of origin: China Package: Retail Box

Specification

Connectors:

external: 1 x 2.5 Gigabit LAN RJ45 jack

internal: 1 x PCI Express x1, V2.1Chipset: Realtek RTL8125AG

Data transfer rate:

Ethernet up to 10 Mbps (Half/Full Duplex)

Fast Ethernet up to 100 Mbps (Half/Full Duplex)

Gigabit Ethernet up to 1000 Mbps (Half/Full Duplex)

NBASE-T with up to 2.5 Gbps (Half/Full Duplex)

PCI Express x1 up to 2.5 Gbps

- Compatible with IEEE 802.3, IEEE 802.3u, IEEE 802.3ab
- Supports Wake On LAN (WOL)
- Supports IEEE 802.1P layer 2 priority encoding
- Supports IEEE 802.3x full duplex flow control
- Supports IEEE 802.1Q Virtual LAN (VLAN)
- Supports 9k Jumbo Frames
- · LED indicator for link and activity
- Operating temperature: 0 °C ~ 60 °C



System requirements

- Linux Kernel 3.2 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC with one free PCI Express slot

Package content

- PCI Express card
- · Low profile bracket
- Driver CD
- User manual

Images











General

Supported operating system: Linux Kernel 3.2 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit

Interface

External:	1 x Gigabit LAN RJ45 jack
Internal:	1 x PCI Express x1, V2.1

Technical characteristics

Chipset:	Realtek RTL8125AG
Data transfer rate:	Ethernet up to 10 Mbps Fast Ethernet up to 100 Mbps Gigabit Ethernet up to 1 Gbps Gigabit Ethernet up to 2.5 Gbps

Physical characteristics

Slot bracket:	Low Profile
	standard