

# Industrial Barcode Scanner 1D and 2D for 433 MHz or Bluetooth with inductive charging station

## Description

This barcode scanner by Delock can be wirelessly connected to a PC, laptop or directly to a mobile phone or tablet. All common **1D and 2D barcode types** can be precisely captured even at long distances. Additionally, the scanner recognizes barcodes displayed on displays and monitors.

### Automatic adaptation to ambient brightness

The scanner automatically adapts to the ambient brightness and captures **up to 120 scans per second** under optimal lighting conditions.

In low ambient brightness, the barcode is illuminated by an additional white LED and can therefore also be used in poor lighting conditions.

### Sturdy processing

Due to its sturdy design, the scanner can easily absorb **falls up to 1.80 m** and is therefore ideally suited for use in industrial environments.

### Charging station acts as interface

The data transfer of the scanned barcodes is done either via **Bluetooth** or via the **433 MHz frequency band**. In addition to charging the hand scanner, the scanner's **inductive charging station** also functions as a 433 MHz interface and is connected to the system via a USB cable.

### Please Note

Not suitable for Swiss QR Codes.



**Item no. 90586**

EAN: 4043619905867

Country of origin: China

Package: Box

## Technical details

- **Charging station**
- Connector: 1 x USB 2.0 Type-A male
- Input voltage: 5 V
- Current consumption:  
operation: max. 1100 mA

- standby: max. 700 mA
- Operating temperature: -20 °C ~ 50 °C
- Storage temperature: -40 °C ~ 70 °C
- Relative humidity: 5 - 95 % (non condensing)
- Colour: black
- Weight: ca. 295 g
- Dimensions (LxWxH): ca. 180 x 100 x 75 mm
- Cable length without connectors: ca. 1.25 m
- Bluetooth standard V 4.1
- 433 MHz

**Barcode scanner**

- Decoding chip: ARM Cortex 32 Bit
- Rechargeable battery: Li-Polymer battery 1800 mAh
- Resolution: max. 1280 x 800
- Trigger: scan button
- Reading distance: ca. 30 mm to 500 mm
- Reading accuracy: 3 - 4 mil
- Range:
  - Bluetooth: up to 10 m
  - 433 MHz: up to 100 m
- Internal memory: 16 MB
- Scan type: LED
- Light colour: visible LED red
- Compensation light: LED white
- Sensor: CMOS image sensor
- Scan rate: up to 120 scans per second
- Scan angle: 55°
- Surrounding brightness: max. 100000 Lux
- Input voltage: 5 V
- Current consumption:
  - operation: max. 220 mA
  - standby: max. 20 mA
- Operating temperature: -20 °C ~ 50 °C
- Storage temperature: -40 °C ~ 70 °C
- Relative humidity: 5 - 95 % (non condensing)
- Colour: black / yellow
- Weight: ca. 321 g
- Dimensions (LxWxH): ca. 185 x 100 x 80 mm
- Scancodes:
  - Code 128
  - Code 39
  - Interleaved 2 of 5
  - EAN-8 / EAN-13
  - ISBN - 13
  - Data Matrix
  - Micro PDF417
  - Micro QR
  - PDF417
  - QR Code

---

## System requirements

- Android 11.0 or above
- Bluetooth standard 4.1 or above
- iPad Pro (3rd Generation) or above
- Mac OS 11.6 or above
- Windows 8.1/8.1-64/10/10-64/11
- PC or laptop with a free USB Type-A port for dongle

---

## Package content

- Barcode scanner
- Charging cradle
- User manual

---

## Images



### Technical characteristics

Operating temperature:	-20 °C ~ 50 °C
Current consumption:	operation: 220 mA Standby: 20 mA
Resolution:	1280 x 800 pixel
Scan rate:	120 scan per second
Trigger:	scan button
Reading distance:	30 mm - 500 mm
Sensor:	CMOS Bildsensor
Scancodes:	EAN-8 EAN-13 Interleaved 2 of 5 Codabar Standard Code 39 Full ASCII Code 39 Code 128 MSI Plessey Code PDF417 DataMatrix QR Code Micro QR Code Micro PDF417 ISBN - 13
Surrounding brightness:	100000 Lux

### Physical characteristics

Weight:	321 g
Length:	185 mm
Width:	80 mm
Height:	100 mm
Colour:	black yellow

### Manufacturer information

---

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de

