

Delock 3.5" USB 3.0 Card Reader 5 slot + 4 port USB 3.0 Hub

Descriere scurta

This card reader by Delock can be installed into a 3.5" bay of a PC and will be connected to an internal USB 3.0 pin header male port. It has a 5 slot card reader and enables the connection of up to four USB devices, which the USB 3.0 hub provides.



Nr. 91493

EAN: 4043619914937

Țara de origine: China

Pachet: Retail Box

Specification

- Connector:
 - external:
 - 5 x Card Reader slots
 - 4 x USB 3.0 Type-A female
 - internal:
 - 1 x 19 pin USB 3.0 pin header female
 - 1 x 4 pin power connector
- Chipset: GL3522 (Hub), GL3223 (Card Reader)
- Metal housing for installation into a 3.5" bay
- Data transfer rate up to 5 Gb/s
- 4 port USB 3.0 hub supports USB Battery Charging BC 1.2 specification
- LED indicator for the card reader for power (green) and access (red)
- Cable data:
 - 1 x 19 pin USB 3.0 pin header female cable ca. 53 cm (incl. connector)
 - 1 x 4 pin power cable ca. 29 cm (incl. connector)
- Hot Swap, Plug & Play

• Supports following memory cards:

Slot 1 Compact Flash / Micro Drive	CF I, CF II, CF Extreme, CF Extreme III, CF Extreme IV, Micro Drive
Slot 2 Memory Stick	MS, High Speed Memory Stick (HS MS), MS PRO, MS PRO-HG, Memory Stick XC, MS Duo,

	MS PRO Duo, MS PRO Duo Mark2, MS PRO-HG, MS PRO-HG Duo, MS PRO-HG Duo HX, MS Micro*, MS PRO Micro*, MS-HG Micro*, MS XC-HG Micro*, M2*
Slot 3 xD	xD, xD type M, xD type H
Slot 4 Micro SD	microSD, Micro SDHC, Micro SDHC Ultra, T-Flash
Slot 5 Secure Digital / Multi Media Card	SD, SD Ultra, SD High Capacity (SDHC), SD Ultra, SDHC Ultra, SDXC, SDXC Ultra, MMC, miniSD, MMCmobile, RS-MMC

*Adapter is required

Cerinte de sistem

- Linux Kernel 3.10 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC with one free 3.5" bay
- Motherboard with a free 19 pin USB 3.0 pin header male
- Power supply with a free 4 pin power connector

Pachetul contine

- 3.5" card reader with connection cable
- Screws
- User manual

Imagini



General

Formă:	3.5"
Function:	Înlocuire la cald Plug & Play
Supported operating system:	Linux Kernel 3.10 sau superior Windows 10 32-bit Windows 10 64-bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit

Interface

External:	1 x fantă CF 1 x fantă MS 1 x fantă Micro SD 1 x fantă SD 1 x fantă xD 4 x USB 5 Gbps Tip-A mamă
Internal:	1 x conector mamă cu pini USB 5 Gbps cu 19 pini 1 x conector de alimentare cu 4 pini

Technical characteristics

Chipset:	Genesys Logic
Data transfer rate:	USB 10 Gbps up to 10 Gb/s

Physical characteristics

Colour:	negru
---------	-------