

Delock 5.25" USB 3.0 Card Reader 5 slot + 4 port USB 3.0 Hub incl. V / A indicator and fan control

Descrizione

This card reader by Delock can be installed into a 5.25" bay of a PC and will be connected to an internal USB 3.0 pin header male port. It has a 5 slot card reader and enables the connection of up to four USB devices, which the USB 3.0 hub provides. The LED display indicates the current rating and voltage values of the connected USB devices. In addition, the card reader has a slider for fan control.



Articolo n. 91494

EAN: 4043619914944

Paese di origine: China

Pacchetto: Retail Box

Specifiche

- Connector:
 - external:
 - 5 x Card Reader slots
 - 4 x USB 3.0 Type-A female
 - internal:
 - 2 x USB 3.0 Type-A male
 - 1 x 4 pin power connector
 - 1 x 3 pin fan pin header male
- 1 slider for fan control
- 1 push button to select the USB port, which indicates voltage (V) and current (A)
- Chipset: GL3522 (Hub), GL3223 (Card Reader)
- Plastic housing for installation into a 5.25" bay
- Data transfer rate up to 5 Gb/s
- 4 port USB 3.0 hub supports USB Battery Charging BC 1.2 specification
- LED indicator for the card reader for power (green) and access (red)
- Cable data:
 - 2 x USB 3.0 Type-A female to 1 x 19 pin USB 3.0 pin header female ca. 58 cm (incl. connector)
 - 1 x 4 pin power cable ca. 33 cm (incl. connector)
- Hot Swap, Plug & Play

• Supports following memory cards:

Slot 1	CF I, CF II, CF Extreme, CF
Compact Flash /	Extreme III,

Micro Drive	CF Extreme IV, Micro Drive
Slot 2 Memory Stick	MS, High Speed Memory Stick (HS MS), MS PRO, MS PRO-HG, Memory Stick XC, MS Duo, MS PRO Duo, MS PRO Duo Mark2, MS PRO-HG, MS PRO-HG Duo, MS PRO-HG Duo HX, MS Micro*, MS PRO Micro*, MS-HG Micro*, MS XC-HG Micro*, M2*
Slot 3 xD	xD, xD type M, xD type H
Slot 4 Micro SD	microSD, Micro SDHC, Micro SDHC Ultra, T-Flash
Slot 5 Secure Digital / Multi Media Card	SD, SD Ultra, SD High Capacity (SDHC), SD Ultra, SDHC Ultra, SDXC, SDXC Ultra, MMC, miniSD, MMCmobile, RS-MMC

*Adapter is required

Requisiti di sistema

- Windows 7/7-64/8/8-64/8.1/8.1-64/10/10-64, Linux Kernel 3.7
- PC with one free 5.25" bay
- Mainboard with a free 19 pin USB 3.0 pin header male
- Power supply with a free 4 pin power connector
- Fan with a free 3 pin fan control connection cable

Contenuto della confezione

- 5.25" Card Reader
- 2 x cable
- Screws
- User manual

Immagini



General

Fattore di forma:	5.25"
Function:	Hot Swap Plug & Play
Supported operating system:	Linux Kernel 3.7 o superiore Windows 10 32-bit Windows 10 64-bit Windows 7 32-Bit Windows 7 64-Bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-Bit Windows 8.1 64-Bit
Indicatore LED:	V / A indicator for hub

Interface

External:	1 x slot CF 1 x slot MS 1 x slot Micro SD 1 x slot SD 1 x slot xD 4 x USB 5 Gbps Tipo-A femmina
Internal:	2 x USB 5 Gbps Type-A male 1 x connettore di alimentazione a 4 pin 1 x 3 pin fan pin header male

Technical characteristics

Chipset:	Genesys Logic
Data transfer rate:	USB 10 Gbps up to 10 Gb/s

Physical characteristics

Colour:	nero
---------	------