

Delock SATA 3.5" Card Reader for Compact Flash

Description

This card reader by Delock can be installed into a 3.5" bay or a PC slot of the PC and will be connected to a free SATA port of the motherboard. The Compact Flash card works as additional memory as well as a hard disk for an operating system from which can be booted.



Item no. 91635

EAN: 4043619916351 Country of origin: Taiwan, Republic of China

Package: Retail Box

Specification

- Connectors:
 - external:
 - 1 x CF slot
 - internal:
 - 1 x SATA 3 Gb/s 7 pin plug
 - 1 x 4 pin power connector
- · Chipset: Marvell
- Supports Compact Flash type I, type II or Micro Drive
- Supports +3.3 V or 5 V Compact Flash cards
- For installation into a 3.5" bay or PC slot or low profile PC slot
- Data transfer rate up to 3 Gb/s
- · LED indicator
- · With eject button
- Bootable

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64/11, Linux Kernel 3.7, Mac
- PC with a free 3.5" bay or PC with one free slot
- A free SATA port



Package content

- Card reader SATA to CF
- Installation frame
- Slot bracket
- · Low profile bracket
- 4 pin power cable
- Screws
- User manual

Images









