

Delock 3.5" USB 3.0 Card Reader 4 slot + 1 x USB-C™ female + 3 x USB 3.0-A female

Description

This card reader by Delock can be installed into a 3.5" bay of a PC and will be connected to an internal USB 3.0 pin header male port. It has a four slot card reader and enables the connection of up to four USB devices. The hub has one USB Type-A port, which provides the quick charging function, as well as one USB Type-C™ port.



Note

- Supports SD 4.0 (UHS-II) memory cards

Item no. 91657

EAN: 4043619916573

Country of origin: China

Package: Retail Box

Specification

- Connectors:
 - external:
 - 4 x Card Reader slots
 - 1 x SuperSpeed USB (USB 3.1 Gen 1) USB Type-C™ female
 - 1 x USB Type-A female charging port
 - 2 x SuperSpeed USB (USB 3.1 Gen 1) Type-A female
 - internal:
 - 1 x 19 pin USB 3.0 pin header female
 - 1 x Molex 4 pin male
- Chipset: GL3522 (Hub), RTS5321 (Card Reader)
- Metal housing for installation into a 3.5" bay
- Data transfer rate up to 5 Gbps
- Maximum output current:
 - USB Type-C™ / USB Type-A female 5 V / 1.5 A
 - USB Type-A female charging port 5 V / 2.4 A
- LED indicator for the card reader for power (green) and access (red)
- Cable data:
 - 1 x 19 pin USB 3.0 pin header female cable ca. 53 cm (incl. connector)
 - 1 x 4 pin power cable ca. 28 cm (incl. connector)

- Hot Swap, Plug & Play

- Supports following memory cards:

Slot 1 Compact Flash

CF I, CF II, Micro Drive

Slot 2 Micro SD

MicroSD, Micro SDHC, Micro SDXC, Micro SD UHS-I, Micro SD UHS-II, T-Flash, MMCmicro

Slot 3 Secure Digital / Multi Media Card

SD, SD High Capacity (SDHC), SD UHS-I, SD UHS-II, SDXC, miniSD*, MMC, MMC plus, MMCmobile*, RS-MMC

Slot 4 Memory Stick

MS, MS PRO, MS PRO-HG, Memory Stick XC, MS Duo, MS PRO MagicGate, MS PRO Duo, MS PRO-HG Duo, MS PRO-HG Duo, MS XC-HG Duo, MS XC Duo, MS Micro*, MS PRO-HG Micro*, MS HG Micro*, MS XC-HG Micro*, MS XC Micro*, M2*

*Adapter is required

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 4.x.x
- PC with one free 3.5" bay
- Mainboard with a free 19 pin USB 3.0 pin header male
- Power supply with a free 4 pin power connector

Package content

- 3.5" card reader with connection cable
- Screws
- User manual

Images



General

Function:	Hot Swap Plug & Play
Supported operating system:	Linux Kernel 4.x or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit

Supported memory card:	Micro SD
	Micro SDHC
	SD
	MS Micro
	SDHC
	SDXC
	CF I
	CF II
	Micro Drive
	Micro SD UHS-I
	Micro SD UHS-II
	T-Flash
	MMCmicro
	SD UHS-I
	SD UHS-II
	miniSD
	MMC
	MMC plus
	RS-MMC
	MS
	MS Pro
	MS PRO-HG
	Memory Stick XC
	MS Duo
	MS Pro MagicGate
	MS PRO Duo
	MS PRO-HG Duo
	MS XC-HG Duo
	MS XC Duo
	MMCmobile
	MS PRO-HG Micro
	MS HG Micro
	MS XC-HG Micro
	MS XC Micro
	M2

Interface

Output:	1 x CF type II slot 1 x USB Type-A female 5 V / 2.4 A 1 x Micro SD Slot 1 x SD / MMC slot 1 x MS slot 1 x USB 5 Gbps USB Type-C™ female
Internal:	1 x 19 pin USB 5 Gbps pin header female 1 x 4 pin power connector

Technical characteristics

Chipset:	Realtek RTS5321 Genesys Logic GL3522
Data transfer rate:	up to 5 Gbps