

Delock USB 2.0 Card Reader 3.5" All in 1

Description

This Delock Card Reader can be installed into the 3.5" drive bay of your PC. Besides its classic function it offers you one Power Over eSATA port, one USB 2.0 port, one FireWire port as well as one HD-Audio input and output.



Item no. 91669

EAN: 4043619916696

Country of origin: China

Package: Retail Box

Specification

- USB 2.0 Card Reader 57 in 1 in a metal case for 3.5" bay mounting
- 1 x Power Over eSATA 5 V (eSATAp), 1 x USB 2.0, 1 x FireWire A 6-pin
- HD-Audio Ports: Line-In, Line-Out
- Hot Swap, Plug & Play

- Supports following memory cards:

Slot 1	CF I, CF II, CF 4.0, CF Extreme, CF Extreme III, CF Extreme IV, CF Extreme IV UDMA, UDMA Extreme, UDMA 6 Extreme Pro, ULTIMA II, Micro Drive, Magicstor
Slot 2	SD, SD High Capacity (SDHC), SDXC, SD Ultra II, SD UDMA II, SD Extreme III, SDHC Turbo, SDHC Ultra, SDHC Extreme, SDHC Extreme III, Turbo-SD, Turbo Mini SD*, Mini SD*, Mini SDHC*, MMC-I, MMC-II, MMC plus, MMC plus Turbo, HS-MMC, HC-MMC, MMCmobile*, MMCmobile* Dual-Voltage, RS-MMC*, RS-MMC 4.0*
Slot 3	xD, xD type M, xD type H
Slot 4	MicroSD, Micro SDHC, Micro SDHC Turbo, Micro SDXC, T-Flash, MMCmicro

Slot 5	MS, MS-ROM, MS Magic Gate, MS Pro, MS-Pro Magic Gate, MS-Duo, MS-Duo Magic Gate, MS-Pro Duo, MS-Pro HighSpeed, MS-Pro HG-Duo, MS-Pro Duo Magic Gate, MS Micro (M2)*
---------------	---

* Adapter required

System requirements

- Windows 2000/XP/XP-64/Vista/Vista-64/7/8, Mac OS 8.6x or above, Linux OS 2.4 or above
- PC with one free 3.5 Bay
- One free internal 9-pin USB 2.0 port
- One free internal 4-pin USB 2.0 port
- Internal FireWire, HD-Audio, AC'97, SATA ports

Package content

- Card Reader with cable
- User manual

Images

