

Delock USB 3.0 Card Reader All in 1

Description

This card reader by Delock has four memory card slots and allows to read and write many different memory cards. The card reader can be connected to a PC or laptop via the USB Type-A interface.

Note

• Supports SD 4.0 (UHS-II) memory cards



Item no. 91710

EAN: 4043619917105 Country of origin: China Package: Retail Box

Specification

- Connectors:
 - 1 x USB 3.0 Type Micro-B female >
 - 1 x CF type II slot
 - 1 x Micro SD slot
 - 1 x SD / MMC slot
 - 1 x MS slot
- Chipset: Realtek RTS5321
- Data transfer rate up to:

SuperSpeed USB 5 Gbps,

Hi-Speed 480 Mbps,

Full-Speed 12 Mbps,

Low-Speed 1.5 Mbps

- Supports PIO, DMA, UDMA mode
- Supports UDMA 7
- Supports SD 3.0 (UHS-I), SD 4.0 (UHS-II)
- Dimensions (LxWxH): ca. 85 x 52 x 19 mm
- Hot Swap, Plug & Play
- Supports following memory cards:

Slot 1 Compact Flash



CF I, CF II, Micro Drive

Slot 2 Micro SD

Micro SD, Micro SDHC, Micro SDXC, Micro SD UHS-I, Micro SD UHS-II, T-Flash, MMCmicro

Slot 3 Secure Digital / Multi Media Card

SD, SD High Capacity (SDHC), SD UHS-I, SD UHS-II, SDXC, miniSD, MMC, MMC plus, MMCmobile*, RS-MMC

Slot 4 Memory Stick

MS, MS PRO, MS PRO-HG, Memory Stick XC, MS Duo, MS PRO MagicGate, MS PRO Duo, MS PRO-HG Duo, MS PRO-HG Duo, MS XC-HG Duo, MS XC Duo, MS Micro*, MS PRO-HG Micro*, MS HG Micro*, MS XC-HG Micro*, MS XC Micro*, M2*

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 4.x.x
- PC or laptop with a free USB Type-A port

Package content

- USB 3.0 Card Reader All in 1
- USB 3.0 Type Micro-B to Type-A cable, length ca. 50 cm
- User manual

Images









^{*}Adapter is required



General

Function:	Hot Swap Plug & Play
Supported operating system:	Linux Kernel 4.x or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit
Supported memory card:	Micro SD Micro SDHC Micro SDXC SD SDHC SDXC CF I CF II Micro Drive Micro SD UHS-I Micro SD UHS-II T-Flash MMCmicro SD UHS-II so UHS-II miniSD MMC MMC plus RS-MMC MS MS Pro MS PRO-HG Memory Stick XC MS Duo MS PRO-HG Duo MS YC-HG Duo MS XC-HG Duo MS XC-HG Duo MS XC Duo



Interface

Output:	1 x CF type II slot 1 x Micro SD Slot 1 x SD / MMC slot 1 x MS slot
Input:	1 x USB 5 Gbps Type Micro-B female

Technical characteristics

Chipset:	Realtek RTS5321
Data transfer rate:	up to 5 Gbps

Physical characteristics

Length:	85 mm
Width:	52 mm
Height:	19 mm