

Delock Converter HDMI to 3G-SDI

Description

This converter by Delock can be used to convert an HDMI signal to an HD- or 3G-SDI signal. Different video devices can be connected, e.g. a camera with HDMI output to an HD-SDI recorder. The SDI signal is transmitted via a conventional 75 Ohm coaxial cable with BNC connectors.



Item no. 93238

EAN: 4043619932382

Country of origin: China

Package: Retail Box

Specification

- Connectors:
Input:
1 x HDMI-A female
Output:
2 x BNC female (SDI)
- Chipset: GV7600
- Supports 3G-SDI Level A
- Supported resolution:
SD 480i, 525i and 625i
HD 720p 24, 25, 30, 50 and 60 Hz
HD 1080i 50, 60 Hz
HD 1080p 24, 25, 30, 50 and 60 Hz
- Data transfer rate up to 3 Gbps
- Supports 8 audio channels with 48 kHz PCM
- Robust metal housing
- Power consumption: max. 4 W
- Dimensions (LxWxH): ca. 100 x 70 x 25 mm


Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A
- Output: 5 V / 1 A
- Ground outside, plus inside
- Dimensions:
inside: ø ca. 2.1 mm
outside: ø ca. 5.5 mm
length: ca. 9 mm

Package content

- Converter HDMI to 3G-SDI
- Mounting brackets and screws
- Power supply

Images



Interface

Connector 1:	1 x HDMI-A female
Connector 2:	1 x BNC female
connector 3:	1 x BNC female

Technical characteristics

Chipset:	GV7600
----------	--------

Physical characteristics

Length:	100 mm
Width:	70 mm
Height:	25 mm