



Delock 3G-SDI Switch 4 in > 1 out

Description

With this Delock SDI switch, up to four SDI input sources can be connect to one SDI output device, such as an HD-SDI monitor. By pressing a button on the device, it can be switched from one source to another.



Item no. 93251

EAN: 4043619932511 Country of origin: China Package: White Box

Specification

• Connectors:

Input:

4 x BNC female (3G-SDI)

1 x 5 V DC jack

Output:

1 x BNC female (3G-SDI)

• Supported resolution:

SD 480i, 525i and 625i

HD 720p 24, 25, 30, 50 and 60 Hz

HD 1080i 50, 60 Hz

HD 1080p 24, 25, 30, 50 and 60 Hz

- Configuration and control of the device via RS232 interface
- · Robust metal housing
- Power consumption: max. 3 W
- Dimensions (LxWxH): ca. 162 x 82 x 25 mm

Power supply specification

Wall power supply



• Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A

• Output: 5 V / 1 A

• Ground outside, plus inside

• Dimensions:

inside: ø ca. 2.1 mm outside: ø ca. 5.5 mm length: ca. 9 mm

Package content

• 3G-SDI Switch

• Power supply

Images





