

Delock HD-SDI Outdoorcamera Bullet with Motorzoom

Description

This HD-SDI Surveillance Camera features a high-resolution 2 Megapixel sensor and delivers crystal-clear, uncompressed images with full HD resolution in real time. The HD-SDI output is compatible with other HD-SDI equipment. The signal is transmitted via a conventional 75 ohm coaxial cable with BNC connector, so an already existing infrastructure can be used. The built-in infrared LEDs and automatic day / night switching deliver detailed images even in the dark. For easier installation and operation, the OSD and the motorized zoom and focus can be operated with the supplied RS-485 control unit. The weatherproof enclosure is suitable for indoor and outdoor installation.



Item no. 93252

EAN: 4043619932528

Country of origin: China

Package: Box

Specification

- Connector:
 - 1 x BNC female (HD-SDI: 1920 x 1080p with 25 or 30 Hz, switchable to 1280 x 720p with 50 or 60 Hz, SMPTE 292M)
 - 1 x BNC female (Composite Video: PAL or NTSC)
 - 1 x open cable (RS-485)
 - 1 x DC 12 V Power
- 2 Megapixel Progressive Scan CMOS Sensor (1 / 2.8")
- 2.8 - 12 mm zoom lens (motorized)
- 36 integrated Infrared-LEDs, max. 40 m distance
- Internal cable routing (tamper protection)
- Water resistant enclosure with canopy
- Included PELCO control unit for OSD and zoom over RS-485
- Picture Optimization: Automatic shutter control, automatic gain control (AGC), adaptive colour and contrast adaptation (ACCE), digital noise reduction (3D DNR), highlight and backlight compensation (HLC / BLC), automatic white balance (AWB), automatic day- / night switching
- Operating temperature: -10 ~ +50 °C
- Humidity: 0 ~ 85 % (non condensing)
- Dimensions (LxWxH): ca. 32 x 9.5 x 8.5 cm
- Weight: ca. 0.9 kg

Specification of power connector

- Input: 12 V
- Ground outside, plus inside
- Dimensions:

inside: ø ca. 2.1 mm
outside: ø ca. 5.5 mm
length: ca. 9.5 mm

System requirements

- Device with HD-SDI input or HD-SDI signal converter
 - Power supply with DC 12 V / 1 A (not included)
-

Package content

- HD-SDI Bullet Camera
 - PTZ & OSD Controller
 - Splitter DC 5.5 x 2.1 mm 1 x female > 2 x male
 - Mounting screws and dowels
 - Allen wrench
 - User manual
-

Images

