

Delock Mini PCIe I/O PCIe half size 1 x RJ45 2.5 Gigabit LAN

Description

This Mini PCle module by Delock expands a system by **one 2.5 Gigabit LAN interface**, which can be lead out via the slot bracket.

NBASE-T for higher speed

Modern services and new technologies require higher bandwidths. NBASE-T technology enables speeds of 1 Gbps and 2.5 Gbps with conventional networking cables. The best possible transmission rate is set automatically.



Item no. 95271

EAN: 4043619952717 Country of origin: China Package: Retail Box

Specification

Connectors:

internal: 1 x Mini PCle male

external: 1 x 2.5 Gigabit LAN RJ45 jack

Chipset: Realtek RTL8125B

• Form factor: Mini PCIe half size

• Interface: PCI Express revision 2.1

• Data transfer rate:

Ethernet up to 10 Mbps (Half/Full Duplex)

Fast Ethernet up to 100 Mbps (Half/Full Duplex)

Gigabit Ethernet up to 1000 Mbps (Half/Full Duplex)

NBASE-T with up to 2.5 Gbps (Half/Full Duplex)

PCI Express x1 up to 4 Gbps

- Supports IEEE 802.3 / 802.3u / 802.3ab
- Supports Wake On LAN (WOL)
- Supports IEEE 802.1P layer 2 priority encoding
- Supports IEEE 802.3x full duplex flow control
- Supports IEEE 802.1Q Virtual LAN (VLAN)
- Supports 9k Jumbo Frames
- LED indicator for link and activity



• Cable length with connectors: ca. 25 cm

System requirements

- Windows 8.1/10/11
- Motherboard with a free Mini PCIe slot with a PCIe interface
- PC with one free slot

Package content

- Mini PCIe module
- 2 connecting cable
- Slot bracket
- · Low profile bracket
- Driver CD
- User manual

Images









General

Form factor:	Mini PCIe half size
Supported operating system:	Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows 11

Interface

|--|

Technical characteristics

Chipset:	Realtek RTL8125
Data transfer rate:	Ethernet up to 10 Mbps Fast Ethernet up to 100 Mbps Gigabit Ethernet up to 1 Gbps Gigabit Ethernet up to 2.5 Gbps

Physical characteristics

Cable length incl. connector:	25 cm
Slot bracket:	Low Profile standard