

# Delock USB 2.0 IR Camera Module 5.04 mega pixel 80° V5 fix focus

## Description

The Delock USB 2.0 camera module offers in compact construction low power consumption as well as high resolution. It is ideal for installation in industry components like IPCs, embedded systems, sensors, notebooks, smartphones, tablets or instrument manufacture. You can perform with suitable IR lighting shots in the dark. The use of a photosensitive sensor with back side illumination (BSI) expands the scope of this module.



**Item no. 96367**

EAN: 4043619963676

Country of origin: China

Package:

## Technical details

- Connector: USB 2.0 5 pin jack SMT, 1 mm pitch
- Resolutiob: 5.04 Mega Pixel
- Without optical IR filter
- Standard SCCB interface (I<sup>2</sup>C Bus)
- Output support for RAW RGB, RGB565/555/444, CCIR656, YUV422/420, YCbCr422 and compression
- Maximum resolution: QSXGA (2592 x 1944)
- Automatic image control functions including
  - Automatic exposure control (AEC)
  - Automatic white balance (AWB)
  - Automatic band filter (ABF)
  - Automatic black-level calibration (ABLC)
- Image quality controls including colour saturation, gamma, sharpness (edge enhancement), lens correction, white pixel canceling, noise canceling, and automatic 50/60 Hz luminance detection
- Supports scaling
- Power consumption:
  - Sensor suspend: 90 mA
  - Sensor active: 140 mA ± 5 mA @ 640 x 480 pixel
- Operating voltage: 5 V DC
- Operating temperature: 5 °C ~ 50 °C
- Relative humidity during operation: max. 80 %
- Sensor size: 1/4 inch

- Sensitivity: 0.6 V (lx s)
  - Signal to noise ratio: 36 dB
  - Dynamic range: 68 dB
  - Fix focus: 0.3 m ~ infinite
  - Lens: F/2.5
  - Frame rates:
    - 30 fps @ HVGA, VGA, XGA, 720p, QVGA
    - 15 fps @ UXGA, 1080p, QXGA
    - 7 fps @ 2592 x 1944
  - Dimension (LxWxH): ca. 60 x 8 x 13 mm
- 

## System requirements

- PC with UVC support
  - Windows Vista/ 7/ 8/ 10
  - DirectX 9.0c and above
  - Linux 2.6.15 and above with Video4Linux
  - Minimum CPU P4 1.4 GHz, 512 MB RAM
- 

## Package content

- Camera module
  - CD ROM with user manual
- 

## Images



## General

Supported operating system:	Linux Kernel 2.6.15 and above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows Vista 32-bit Windows Vista 64-bit Windows XP 32-bit
Operating system requirement:	Windows DirectX from 9.0c Linux with Video4Linux

## Interface

Connector:	USB 2.0
------------	---------

## Technical characteristics

Operating voltage:	5 V
Operating temperature:	5 °C ~ 50 °C
Maximum screen resolution:	2592 x 1944 @ 7 fps
Minimum screen resolution:	160 x 144 @ 30 fps
Sensor size:	1/4"
Current consumption:	140 mA @ 640 x 480

## Physical characteristics

Weight:	2 g
Length:	60 mm
Width:	8 mm
Height:	13 mm

### Manufacturer information

---

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de

